



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
H	-	A	INITIAL RELEASE	12NOV2013	GSK BvH
		A1	ECR-14-011671	14AUG2014	GSK BvH

NOTES:
 Tolerances cable lengths:
 0m to 0.5m +30mm
 0.5m to 1.0m +50mm
 1.0m to 3.0m +100mm
 < 3.0m +1.5%



TECHNICAL DATA	
Operating voltage	max. 60 V AC/DC
Operating current per contact	max. 4 A
Locking of ports	Screw thread M8 x 1 mm (recommended torque 0.4 Nm) self-securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)



PUR CABLE	
No./diameter of wires	3 x 0.34 mm ²
Wire isolation	PP (br, bl, bk)
C-track properties	5 million
Jacket	PUR (UL/CSA)
Outer diameter	approx. 5.0 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-40...+80 °C
Temperature range (mobile)	-25...+80 °C

PVC CABLE	
No./diameter of wires	3 X 0.34 mm ²
Wire isolation	PVC (br, bl, bk)
C-track properties	
Jacket	PVC (UL/CSA)
Outer diameter	approx. 5.0 mm
Bend radius (moving)	10 x outer diameter
Temperature range (fixed)	-30...+80 °C
Temperature range (mobile)	-5...+80 °C

3 pos	LENGTH "L"	MATERIAL	JACKET COLOR	TE PN	DESCRIPTION	ITEM
3 pos	10mtr	PVC	Black	1-2273005-4	3x22AWG PVC 10.0m	8
	5mtr			1-2273005-3	3x22AWG PVC 5.0m	7
	3mtr			1-2273005-2	3x22AWG PVC 3.0m	6
	1.5mtr			1-2273005-1	3x22AWG PVC 1.5m	5
3 pos	10mtr	PUR	Black	2273005-4	3x22AWG PUR 10.0m	4
	5mtr			2273005-3	3x22AWG PUR 5.0m	3
	3mtr			2273005-2	3x22AWG PUR 3.0m	2
	1.5mtr			2273005-1	3x22AWG PUR 1.5m	1

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DWN: 12NOV2013 SATHISH KUMAR .G	STE TE Connectivity
	0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -	CHK: 12NOV2013 B.VELDHOVEN APVD: 12NOV2013 A.VAN ZANDVOORT	
MATERIAL: -	FINISH: -	PRODUCT SPEC: 108-19483	NAME: M8 X 1.0 STRAIGHT SOCKET PIGTAIL SHLD
		APPLICATION SPEC: 114-32127	SIZE: A3
		WEIGHT: -	CAGE CODE: 00779
		CUSTOMER DRAWING	DRAWING NO: C-2273005
			RESTRICTED TO: -
			SCALE: NTS
			SHEET: 1 OF 1
			REV: A1